10 SR 2 CP 4Ω

Subwoofer

10" | 400 W


Code Z006006C

SNDW 2" Sandwich voice coil Fiberglass former
Rubber surround
Waterproof Cone Treatment
Ferrite Magnet Circuit
Ventilated Magnet to reduce Power Compression
89.1 dB sensitivity
Frequency Range 30-1500 Hz

⊅270.0







Constructive Characteristics		
Magnet	Ferrite	
Basket Material	Aluminium Die-Cast	
Voice Coil Winding Material	Copper	
Voice Coil Former Material	Fiberglass	
Cone Material	Paper	
Cone Treatment	Surface Waterproof Treatment	
Surround Material	Rubber	
Dust Dome Material	Solid Paper	
Mounting Information		
Overall Diameter	270 mm	
Baffle Cutout Diameter	232 mm	
Mounting Holes	8 holes ø6 on ø252 mm	
Total Depth	121.9 mm	

(1) Rated Power measured with 2-hour test with pink noise signal, 6dB crest factor, loudspeaker in free air, power calculated on rated Zmin. (2) Power on Continuous Program is defined as 3dB greater than the Rated Power. (3) Calculated by Thiele & Small parameters, for SPL average in box refer to frequency response. (4) Thiele & Small parameters measured with laser system after preconditioning test. (5) Measured with respect to a THD of 10%. (6) Value corresponding to a decay of the Force Factor, or Compliance, or both, equal to the 50% of the small signal value. (7) Drawing dimensions: mm.

Due to continuing product improvement, the features and the design are subject to change without notice.



230.0

General Speci	fications		
Nominal Diameter			268 mm (10")
Nominal Impedance			4 Ω
Rated Power AES ⁽¹⁾			200 W
Continuous Program Power ⁽²⁾			400 W
Sensitivity @ 1W	/1m ⁽³⁾		89.1 dB
Voice Coil Diameter			50 mm (2")
Voice Coil Winding Depth			21 mm
Magnetic Gap Depth			8 mm
Flux Density			1.01 T
Magnet Weight			930 g
Net Weight			3.2 kg
Thiele & Small	Parameters ⁽⁴⁾		
Re	3.1 Ω	Fs	31.2 Hz
Qms	4.92	Qes	0.52
Qts	0.47	Mms	61.9 g
Cms	419 µm/N	Bxl	8.54 Tm
Vas	68.5 l	Sd	339.8 cm ²
X max ⁽⁵⁾	+/-7.0 mm	X var ⁽⁶⁾	+/-9.0 mm
ηο	0.38 %	Le (1kHz)	0.88 mH

Ø121.0